

# SANDYLUX

## PALM 63-10



### Description

Protective glove against mechanical risks.  
15G green polyamide-lycra with new generation microporous nitrile palm coated glove

### Standards

Gloves conform to the requirements of PPE Directive 89/686/EEC and to the European standards EN420 and EN388

### Composition

Coating: nitrile.  
Liner: polyamide/lycra  
Binding: polyester



Breathable

ISO 9001 Quality

### Benefits

#### Breathable

- 15G green polyamide-lycra with new generation microporous nitrile palm coated glove.
- A flexible, light glove that absorbs perspiration without reducing the tactile feel.
- Seamless liner.
- Excellent dexterity, sensitivity and tactility, combining a long-life glove, reaching a maximum dexterity level (5), and absolute and maximum abrasion resistance.
- High tear resistance.
- An elastic cuff ensures a secure fit, preventing dirt.
- Tested for harmful substances according to Oeko-Tex® standard 100
- Applications: maintenance, assembly, using tools and instruments, logistics, automotive industry, mining, etc.



### Sizes

6	(XS)	Length: 220 mm
7	(S)	Length: 230 mm
8	(M)	Length: 240 mm
9	(L)	Length: 250 mm
10	(XL)	Length: 260 mm
11	(XXL)	Length: 270 mm

### Additional information

Thickness: 15G  
Weight: 30 g/glove

### Packaging unit

144 pairs per box  
12 pairs per polybag  
Supplied with hang tag (individual)