

DURALUX

3/4 COATED 60-11



Description

Protective glove against mechanical risks. 15G blue nylon/lycra with new generation spraying nitrile 3/4 coated glove

Standards

Gloves conform to the requirements of the EU Regulation 2016/425 and to the European standards EN420 and EN388

Composition

Coating: Microporous sandy nitrile.
Liner: Nylon/lycra
Cuff: Nylon/lycra + elastic
Binding: Polyester

Benefits

The glove that breaths.
So you feel safe and protected!

- A thin, light glove that absorbs perspiration without reducing the tactile feel. Seamless knit nylon/lycra liner.
- Excellent dexterity, sensitivity and tactility, combining a long-life glove, reaching a maximum dexterity level (level 5), absolute and maximum abrasion resistance, tripling the maximum requirement for level 4 (21.000 abrasion cycles), getting maximum grip even in adverse conditions and keeping the maximum touch, as our second skin. We don't know if someone can do it, but Digitx® can get it!
- Seals and protects the hand against mechanical risks while remaining flexible.
- Surface enables a secure grip on slippery objects. Designed for easy movement and continuous wear. Extended protection and precision handling.
- Greater hygiene thanks the **anti-microbial** treatment: long-lasting, safe and fresh wearing comfort.
- Extra-long knitted wrist helps to prevent dirt and debris from entering the glove.
- Applications: handling of small components, maintenance, assembly, using tools and instruments, logistics, automotive industry, mining, general building, construction, agriculture, ...



NITRILE	NYLON	LYCRA	15G	BREATHABLE	EN 388
3/4 COATING	25 g	5 DEXTERITY	TOUCH		4131X



The coating does not go through the liner

Sizes

6/XS 7/S 8/M 9/L 10/XL 11/XXL

Packaging unit

144 pairs per box | 12 pairs per polybag
Supplied with hang tag (individual)