DFYCUT-I7 64-24

Description

Protective glove against mechanical risks. 18G UHMWPE(staple fibre)/steel/polyester/spandex liner with first full nitrile smooth coated plus nitrile sandy finish palm coated glove

Standards

Gloves conform to the requeriments of the EU Regulation 2016/425 and to the European standards EN ISO 21420:2020, EN388:2016+A1:2018 & EN407:2020

Composition

Coating: Sandy nitrile Liner: UHMWPE Binding: Polyester

Benefits

Extra thin & breathable

- 18G UHMWPE(staple fibre)/steel/polyester/spandex liner with first full nitrile smooth coated plus nitrile sandy finish palm coated glove
- Oil and water repellent. Durable and flexible
- Enhanced grip: It is made of rough nitrile.
- Unrivaled dexterity, sensitivity and tactility, combining a long-life glove, reaching a maximum dexterity level (level 5), absolute and maximum abrasion resistance and keeping the maximum touch, as our second skin.
- Super grip in both dry and oily working conditions.
- Snug fit. It seals and protects the hand against mechanical risks while remaining flexible.
- Breathable.
- Knitted extra-long wrist helps to prevent dirt and debris from entering the glove.
- EN407: Heat resistant up to 100°C...
- Applications: Ideal for handling in wet, oily and greasy environments, dirty environments, assembly, building, construction, carpentry, machinary, automotive, etc.

EXTRA GRIP!

Rough finish on the palm





















EN388:2016





DEXTER









6/XS 7/S 8/M 9/L 10/XL 11/XXL

Packaging unit

144 pairs per box 1 12 pairs per polybag Supplied with hang tag (individual)